

Lowboy Power Unit - Kubota Diesel Engine

9505609

• Pressure and Tank Unit • Designed for Use on a Lowboy Trailer or Detached Trailer • Takes the Place of a Hydraulic Wet Kit on a Semi • Battery Included, Electric Start • Painted Black • 1/2" 4 Hole Bolt Down on Frame (Reference Drawing Below for Dimensions) • Heavy Duty Frame • Suction Filter: 100 Mesh Suction Filter with 3 PSI Bypass • Gauge: Liquid Filled S.S. Case 0-5000 • Tank: 12 Gallon Nominal, 10 Gallon Usable, Fully Baffled, 12 Gauge Steel • 5" Level Sight/Temperature Gauge Standard • Relief Valve Adjustable from 100-3000 PSI • Relief Valve: Preset to Power Units' Maximum Pressure Capability (3000 PSI) • High Performance Pressure Balanced Aluminum Body Gear Pump • Tank Drain Plug: #8 O-ring • Fully Tested Before Shipment, Engine Oil Onboard • Anti-Wear ISO 46 Hydraulic Oil Recommended, ATF Satisfactory • Replacement Components Available From Stock

Specifications

- Kubota Diesel Motor with Electric Start
- 12 Gallon Hydraulic Tank (10 Gallon Usable)
- High Efficiency Pressure-Balanced Aluminum Gear Pump
- Provides 4.6 GPM at 3000 PSI
- #12 SAE O-Ring Ports (Pressure & Tank)
- #8 SAE O-Ring Drain Port
- Relief Valve, Adjustable From 100-3000 PSI
- 0-5000 PSI Liquid Filled Pressure Gauge
- Filler Breather Integral
- Suction Filter With 3 PSI Bypass
- 10 Micron Return Filter
- Painted Black
- Engine Oil Onboard
- Fully Tested Before Shipment
- 32-1/2" X 23-3/4" X 19-1/2" (L X W X H)
- 260 Lbs Dry Weight



Stock Number	HP	GPM	PSI	Pressure Gauge	Tank Capacity	P & T Ports	Dimensions L x W x H	Ship Wt.
9505609	9.5	4.6	3000	0-5000 PSI	10 Gallons	#12 SAE O-Ring	32.50" x 23.75" x 19.50"	360

